

MP 6002  
MP 7502  
MP 9002

DIGITAL MULTIFUNCTION COPIER



**MP 6002**

60  
ppm

B/N

**MP 7502**

75  
ppm

B/N

**MP 9002**

90  
ppm

B/N

**GENERAL**

Copying process	Four laser beams & electro-photographic printing
Copy speed	60/75/90 copies per minute (A4)
Resolution	1,200 dpi
Multiple copy	Up to 999
Warm-up time	Less than 30/30/300 seconds
First copy speed	Less than 3.9/3.2/2.9 seconds
Zoom	25 - 400% (in 1% steps)
Memory	Standard 1 Gb – Max. 1.5 GB + 250 GB Hard Disk Drive
Paper input capacity	Standard 2 x 1,550-sheet paper tray(s), 2 x 550-sheet paper tray(s), 100-sheet bypass tray Max. 8,300 sheets
ADF capacity	150 - 250 sheets (less than 80 - 69 g/m <sup>2</sup> )
Paper output	Standard 500 (A4), 250 (A3) sheets
Paper size	A6 - A3
Paper weight	Paper trays 52.3 - 216 g/m <sup>2</sup>
Bypass tray	52.3 - 216 g/m <sup>2</sup>
Duplex tray	64 - 169 g/m <sup>2</sup>
Dimensions(WxDxH)	690 x 790 x 1,171 mm
Weight	Less than 214 kg
Power source	220 - 240 V, 50 - 60 Hz
Power consumption	Max. 1.9/1.9/1.9 Kw

**PRINTER (OPTION)**

Print speed	60/75/90 prints per minute
Printer language	Standard RPCS, PCL5e, PCL6, Option Adobe® PostScript™ 3
Interface Standard	Ethernet 10 base-T/100 base-TX, USB 2.0, Option Parallel port IEEE1284, Wireless LAN (IEEE802.11 a/b/g), Bluetooth, 1000 base-T Ethernet
Memory	1.5 GB + 250 GB Hard Disk Drive
Network protocol	IPv4, IPv6, IPX/SPX, SMB, Apple Talk
Supported Environments	Windows® XP, Windows® Vista, Windows® 7, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008R2 Macintosh OS X Native v10.2 osuccessivo UNIX Sun® Solaris: 2.6, 2.7, 2.8, 2.9, 2.10 HP-UX: 10.x, 11.x, 11i v2, 11i v3 SCO OpenServer: 5.0.6, 5.0.7, 6.0 RedHat® Linux Enterprise: 4, 5, 6 IBM® AIX: 5L V5.3, V6.1, V7.1

**SCANNER (OPTION)**

Scan speed	Black and White : 90 ipm (Simplex) / 178 ipm (Duplex) Color : 90 ipm (Simplex) / 178 ipm (Duplex)
Resolution	Max. 600 dpi (TWAIN 1,200 dpi)
Original size	Max. 279 mm x 432 mm
Output formats	PDF, TIFF
Bundled drivers	Network TWAIN
Scan to e-mail	SMTP, TCP/IP
Destination addresses	Max. 500 per job
Stored destination	Max. 2,000
Scan to folder	Via SMB, FTP or NCP protocol
Destination	Max. 50 folders per job

**FAX (OPTION)**

Circuit	PSTN, PBX
Compatibility	ITU-T (CCITT) G3, ITU-T (T.37) Internet fax, ITU-T (T.38) IP fax
Modem speed	Max. 33.6 Kbps
Resolution	Standard/detail 200 x 100 - 200 dpi
Option	400 x 400 dpi
Compression method	MH, MR, MMR, JBIG
Scanning speed	Less than 0.70 seconds
Memory capacity	Standard 4 MB, Option 28 MB
Memory backup	Yes (one hour)

**OTHER OPTIONS**

4,000-sheet A4 LCT, LG tray for A4 LCT, Multi-folding unit, 3,000-sheet finisher with 50-sheet stapler, 3,000-sheet finisher with 100-sheet stapler, 2,000-sheet saddle-stitch unit with 50-sheet stapler, 9-bin mailbox, Several punch units, Jogger unit for finisher, GBC StreamPunch™ III, Plockmatic booklet maker, @Remote, GlobalScan NX, G3 interface unit, Data Overwrite Security Unit, HDD Encryption Unit, Copy Data Security Unit, VM Card, Browser Unit, Key counter and card bracket  
 Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.  
 For availability of models, options and software, please consult your local Ricoh supplier.

